

FOGH MARINE



Laser 2 Line & Wire Information

<u>Description</u>	<u>Diameter</u>	<u>Line Type</u>	<u>Length</u> [Ⓟ]
LINE			
Mainsheet	5/16" (8mm)	Multifilament Polypropylene	30'
Jib Sheet	5/16" (8mm)	Multifilament Polypropylene	24'
Boom Vang	3/16" (5mm)	Pre-Stretched Polyester	13'
Traveler	3/16" (5mm)	Pre-Stretched Polyester	14'
Main Cunningham	3/16" (5mm)	Pre-Stretched Polyester	4'
Jib Cunningham	3/16" (5mm)	Pre-Stretched Polyester	9'
Outhaul	3/16" (5mm)	Pre-Stretched Polyester	12'
Clew Tie Down	5/32" (4mm)	Pre-Stretched Polyester	2'
Forestay Line	5/32" (4mm)	Pre-Stretched Polyester	2'
Spinnaker Sheet	3/16" / (5mm)	Pre-Stretched Polyester	45'
Spin Pole Topping Lift	5/32" (4mm)	Pre-Stretched Polyester	21'
Spin Pole Trolley	3/16" (5mm)	Shock Cord	15'
Trapeze Shock Cord	3/16" (5mm)	Shock Cord	13'
Jib Halyard Tail	#4 Cord	Cordage	15'
Main Halyard	3/16" (5mm)	Pre-Stretched Polyester	45'
WIRE			
Forestay	3/32" – 1x19 SS	Nicro pressed at both ends with thimbles	13' 7-1/4" *
Shroud (old)	3/32" – 1x19 SS	Nicro pressed at both ends with thimbles	12' 4-3/8" *
Shroud (new)	1/8" – 1x19 SS	Swaged at both ends with MS eyes	12' 3-1/4" *
Jib Halyard (for tooth rack)	3/32" – 7x19 SS	Nicro pressed at one end with thimble, 3" loop with nicro press at other end.	12' 5-1/2" *
Trapeze Wire (eye to eye, new)	3/32" – 7x19 SS	Nicro pressed at both ends with thimbles.	11' 10-1/2"*
Diamond Wires (for use with tang)	3/32" – 1x19 SS	Swaged at one end with MS eye and stud at other end.	12' 8" *
Centerboard Carpet	2 for top 2 for bottom		14" each

* Measurement is bearing point to bearing point with turnbuckle half way open.

[Ⓟ] These are FogH Marine recommended line lengths. If you would like a different line length, please advise at time of ordering. **FogH Marine cannot be held responsible for incorrect line lengths.**

For more information please feel free to contact us at info@foghmarine.com