

FOGH MARINE



Laser Pro Line Information

2002 to Present Racing Lengths

<u>Description</u>	<u>Diameter</u>	<u>Line Type</u>	<u>Length</u> [Ⓟ]
Mainsheet	7mm	"Rooster" Rope	48'
Boom Vang A*	1/8" (3mm)	Solid Spectra	4'
Boom Vang B*	3/16" (5mm)	Spectra	11'
Traveller	3/16" (5.5mm)	Kevlar	12'
Cunningham C*	3/16" (5mm)	Solid Spectra	13'
Cunningham D *	1/8" (3mm)	Solid Spectra	3'
Outhaul E*	3/16" (5mm)	Spectra	13'
Outhaul F*	1/8" (3mm)	Solid Spectra	8' 6"
Clew Tie Down	1/8" (3mm)	Solid Spectra	2'
Daggerboard Shock Cord	3/16" (5mm)	High Stretch Shock Cord	10'
Hiking Strap Adjustment Line	3/16" (5mm)	Pre-Stretched Polyester	4'
Hiking Strap Retainer	3/16" (5mm)	High Stretch Shock Cord	3'
Rudder Downhaul	5/32" (4mm)	Pre-Stretched Polyester	4.5'
Mast Retaining Line	5/32" (4mm)	Pre-Stretched Polyester	2' 6"

[Ⓟ] These are Fogh Marine recommended line lengths. If you would like a different line length, please advise at time of ordering. ***Fogh Marine cannot be held responsible for incorrect line lengths.***

* The new "Laser Performance Upgrade" for the Boom Vang, Cunningham and Outhaul are in "2" pieces. "A" connects to the boom and "B" is the hand held adjustment portion, "C" is in the Cunningham purchase and "D" is through the sail, "E" is the bitter end and "F" is the part attached to the main.

For more information please feel free to contact us at info@foghmarine.com